

Ref: SSS 14.1.1

**SPECIFICATION SELECTION SHEET**  
**MODEL 441-S, 441-SR, 441-X57, 441-VPC**  
**INDUSTRIAL & DISTRIBUTION PRESSURE REGULATOR**



Energy Metering

441 Models	Description	Code
441-S	Low Pressure Regulator	A1
441-SR	Low Pressure Regulator w/relief valve	A2
441-57S	'Roll-out' Diaphragm Regulator	A3
441-X57	High Pressure Regulator	A4
441-VPC	Pilot Operated Regulator	A5

Pipe Size	Code
2"	B1
3"	B2
4"	B3
6"	B4
8"	B5

Dia. Case Size	Code
10"	C1
12"	C2
14"	C3
16"	C4
18"	C5
20"	C6

Spring Color	Code
Aluminium	D1
Green	D2
Yellow	D3
Gray	D4
Blue	D5
Red	D6
Brown	D7
Black	D8
Brown/White	D9

Body Type	Working Pressure psi	Code
Screwed End 2"	250	E1
Flanged ANSI 125lb FF	175	E2
Flanged ANSI 250lb RF	575	E3
Flanged ANSI 300lb RF	720	E4
Flanged ANSI 600lb RF	1200	E5

  

Valve Seat	Material	Code
Single	Stainless Steel	F1
Double	Stainless Steel	F2
Double	Brass	F3

Valve Type	Code
Standard	G1
V-Port	G2

Valve Size	Code
1"	J1
1½"	J2
1¾"	J3
2 1/8"	J4
3"	J5
4 ¼"	J6
5 ¾"	J7
7 1/8"	J8

Pressure	PSIG, kPa, BAR
Inlet	
Outlet (Min)	
Outlet (Max)	

Special Instructions:

Please reference specification bulletin R 1350/1360/1361/1370 for full specification details.  
 Please circle your choice in each category or include code choices on your purchase order.  
 Standard Construction and Testing at Manufacturer's Recommended settings will apply unless otherwise specified above.

<b>Purchase Order No.</b>	
---------------------------	--