

Ref: SSS 17.1.1
SPECIFICATION SELECTION SHEET
AUTO-ADJUST®
TURBINE METER



Energy Metering

Auto-Adjust® Models	Description	Code
4" AAT - 18/27	Flanged, custody transfer meter	A1
6" AAT - 35/57	Flanged, custody transfer meter	A2
8" AAT - 60/90	Flanged, custody transfer meter	A3
12" AAT - 140/230	Flanged, custody transfer meter	A4
100mm AAT - 18/27	Flanged, custody transfer meter	A5
150mm AAT - 35/57	Flanged, custody transfer meter	A6
200mm AAT - 60/90	Flanged, custody transfer meter	A7
300mm AAT - 140/230	Flanged, custody transfer meter	A8

Working Pressure PSI/Bar	Code
175 / 12	B1
220 / 16	B2
275 / 19	B3
720 / 50	B4
1440 / 100	B5

Meter Index	Code
Circular Reading (VCR) [Lexan]	D1
Direct Reading (VDR) [Lexan]	D2
Direct Reading (VDR) [Aluminium]	D3
Direct Reading – Slot Sensor	D4

Options	Code
Slot sensor (Conduit)	E1
Slot sensor (Bendix)	E2
Blade tip sensor	E3

Accessories	Code
No Barriers/enclosures	F1
Yes Barriers/enclosures	F2

Calibration	
Pressure (please state)	
No of points (5 if not specified)	
PROM Chip required (Y/N)	
SER required (Y/N)	

Special Instructions

Please reference specification bulletin M-1073 for full specification details.
 Please circle your choice in each category or include code choices on your purchase order.
 Standard Construction and Testing at Manufacturer's Recommended settings will apply unless otherwise specified above.

Purchase Order No.	
---------------------------	--