


## Model W-2000 DRS

Bronze Magnetic Drive Flanged Ends Size 6" (DN 150mm)



Intelligent Communications Encoder (ICE) Register



W-2000 DRS Turbo Meter

### Description

**Model:** W-2000 DRS Turbo Meter is based on the turbine principle of measurement; its operating range is from 30 to 2000 gallons per minute (6.8 to 450 m<sup>3</sup>/h) with registration accuracy of 100% ± 1.5% of actual thruput.

**Conformance To Standards:** Sensus Turbo Meters comply with ANSI/AWWA Standard C701 (most recent revision). Each meter is performance tested to insure compliance.

**Performance:** The meter's unique principle of measurement assures extended accuracy life. The W-2000 DRS has no restrictions as to sustained flow rates within its operating range. The design permits continuous operation up to its rated maximum flow capacity, without affecting long-term accuracy or causing undue wear.

**Construction:** The meter consists of two basic assemblies—the maincase and the measuring chamber. Straightening vanes in the maincase minimize the swirl upstream of the meter so as to direct the flow evenly to the rotor. The measuring chamber assembly includes the rotor, adjusting vane (for calibration) and sealed Direct Reading (DR) register. The meter includes a built-in strainer with plugged, inlet flush outlets and test plug.

**Magnetic Drive:** The patented Right Angle Magnetic Drive eliminates conventional worm or miter gears normally required for horizontally mounted rotors or turbine measuring elements. Registration is accomplished by combining the magnetic actions of a driver magnet (embedded in the rear face of the rotor), a three-legged flux carrier and a cylindrical follower magnet attached to the gear train shaft inside the register's magnet well. Water flowing through the meter causes the rotor (with magnet) to turn. As one of the magnet poles passes one of the flux carrier legs, the magnetic force is transmitted through the flux carrier leg to the follower magnet, causing the register shaft to rotate. The only moving part in water is the rotor assembly.

**Rotor:** The thermoplastic rotor with graphite bearing rotates on a chrome plated stainless steel shaft. The rotor assembly is virtually weightless in water, thus adding to bearing life.

**Maintenance:** The measuring chamber and straightening vanes can be removed, repaired and/or replaced without disturbing the maincase in the line. A spare chamber can be utilized in the event maintenance is required. Cover plates are also available to keep the line in service while the measuring chamber is repaired and recalibrated. Opposing plugged flush outlets are located on the inlet side of the strainer screen so debris may be discharged efficiently without removing the screen or disturbing the measuring chamber. A test plug is conveniently located on top of the maincase for field testing. Factory testing, repair and measuring chamber exchange programs are available. See Sensus data bulletin TM-699 for details.

### Specifications

<b>SERVICE</b>	Measurement of potable cold water with flow in one direction only.
<b>OPERATING RANGE</b>	Continuous Flows: 30 to 2000 gpm (6.8 to 450 m <sup>3</sup> /h) Intermittent Flows: 2500 gpm max. (562 m <sup>3</sup> /h)
<b>ACCURACY</b>	100% ± 1.5% of actual thruput
<b>LOW FLOW</b>	95% at 20 gpm (4.56 m <sup>3</sup> /h)
<b>PRESSURE LOSS</b>	6.2 psi at 2000 gpm (.4 bar at 450 m <sup>3</sup> /h)
<b>MAXIMUM OPERATING PRESSURE</b>	150 psi (10.0 bar)
<b>FLANGE</b>	6" U.S. ANSI B-16.1 Class 125. Optional drillings, if specified, British Standard B.S. 10 or Metric Standard ISO R2084
<b>REGISTER</b>	Hermetically Sealed Direct Reading Register with Low Flow Indicator. Remote reading unit optional.
<b>METER REGISTRATION</b>	1,000,000,000 gallons 1,000 gallons/sweep hand revolution 100,000,000 cubic feet 100 cubic feet/sweep hand revolution 1,000,000 m <sup>3</sup> 1 m <sup>3</sup> /h sweep hand revolution
<b>MATERIALS</b>	Maincase—Bronze Measuring Chamber—Thermoplastic Straightening Vanes—Thermoplastic Rotor—Thermoplastic Radial Bearing—Graphite Trim—Stainless Steel Thrust Bearings—Tungsten Carbide Magnets—Ceramic Strainer Screen—Stainless Steel Strainer Cover—Bronze Strainer Flush Plugs (2)—1" Tapered Pipe Threads Test Plug—2" Tapered Pipe Threads


**Strainer:** The Model W-2000 DRS Turbo Meter is designed with an integral “V” shaped stainless steel strainer built into its inlet end. A removable cover plate permits easy access to the strainer for routine cleaning.

**Electronic Registers:** Impulse Contact Registers and High Speed Pickup Registers are available for use with Act-Pak<sup>®</sup> Instruments for remote monitoring and control, based on flow rate and/or totalization. See data sheets E-1112 and E-1116.



## Model W-2000 DRS

Bronze Magnetic Drive Flanged Ends Size 6" (DN 150mm)

**Head Loss Curve**



**Accuracy Curve**



Meter and Pipe Size	Normal Operating Range GPM Minimum Maximum		Connections	Dimensions								Net Weight	Shipping Weight
				A	B	C	D	E	F	G	H		
6" DN 150mm	30 6.8m <sup>3</sup> /h	2000 <sup>①</sup> 450m <sup>3</sup> /h	Flanged	27"	13"	7/8"	11"	5-3/4"	9-1/2"	8	3/4"	140 lbs.	165 lbs.
				685.8mm	227mm	22mm	229mm	121mm	191mm	8	16mm	63 kg	74 kg

<sup>①</sup> For continuous flows; 1250 GPM (285m<sup>3</sup>/h) maximum for intermittent flows.

## Remote Reading Systems

For use with all sizes of Sensus Water Meters

All Sensus AMR systems work with the same absolute encoder Electronic Communications Registers (ECR), enabling the utility to mix and match or easily move from one system to another without changing registers for each.

**The TouchRead<sup>®</sup> Automated Meter Reading and Billing System**—is a multipurpose encoder remote system suitable for indoor and/or outdoor use. The ECR Register uses a wired connection between the meter and an outside remote for inside set meters—or a pitlid mounted module, enabling underground meters to be read automatically without opening the meter box or vault. All wired connections and terminals of the TouchRead PitLid (TR/PL) modules and registers are fully sealed at the factory using a special process to ensure protection from water infiltration. The connection terminals of ECR/WP registers are also factory sealed.

Meters equipped for TouchRead System reading can be read with a visual reading device, stand alone AutoGun, and/or reading gun with an AutoRead HandHeld Device. For more information on TouchRead System equipment refer to bulletins AMR-TR, AMR-401, AMR-403, AMR-312 and EXSUMHH.

**PhonRead<sup>®</sup> AMR**—is a reliable telephone based call-in system that does not require batteries for operation. It also does not require equipment to be installed at telephone company facilities. PhonRead Meter Interface

Units (MIU) automatically call "in" to the utility office for transferring meter reading data from the meter site to a PC. PhonRead is a transparent AMR system that does not interfere with customers' telephone service. For more information refer to bulletins AMR-PR and AMR-302.

**RadioRead<sup>®</sup> AMR**—uses superior Direct Sequence Spread Spectrum modulation to provide reliable, safe and virtually interference free radio-based transmission of reading data from underground or inside-set meters that are equipped with Meter Transceiver Units (MXU). A choice of meter reading options is available. A radio frequency hand-held device (RF-HHD) can be used by a meter reader on foot. The RF-HHD can also be used to collect readings from TouchRead equipped meters, or for manual meter reading entries. A more powerful Vehicle Transceiver Unit (VXU) can be used in any car or truck to read meters while on the move. (A dedicated meter reading vehicle is not required.) For more information refer to bulletins AMR-RR, AMR-301 and AMR-303, and AMR-401.

**MultiRead<sup>®</sup> Port Expanders**—can provide the capability to connect multiple ECR equipped meters to a single PhonRead MIU or RadioRead MXU to save the utility time and money for installations such as apartment complexes and shopping centers. Refer to bulletin AMR-305, AMR-306 and AMR-308.

**AUTHORIZED SENSUS DISTRIBUTOR**



P.O. Box 487 • 450 N. Gallatin Avenue  
Uniontown, PA 15401  
1-800-METER-IT • 1-800-638-3748

Fax: Direct to Factory  
Local: 724-439-7729 • Toll Free: 1-800-888-2403

www.sensus.com (select "North America Water")

Email: h2oinfo@sensus.com